



Slats joined transversely by a viewed round tube and available in different widths (A,B) and separations (C).

It is possible to place registrable panels of simple handling.



#### ACOUSTIC TEST



Medium absorptive coefficient

$\alpha_m = 0.85$

Average absorptive coefficient

$\alpha_w = 0.80$

Noise reduction coefficient

NRC = 0.80

#### STUDIED DATA

**Sizes:** 1800X600 mm

**Slats:** 22x90 mm

6 units (rear: 3 units)

**Weight:** 10.92 kg

**Density:** 490 kg/m<sup>3</sup>



Test Sample.

#### TECHNICAL FEATURES

|                           |                                                                             |
|---------------------------|-----------------------------------------------------------------------------|
| <b>Sizes</b>              | 2380x600 (42/68/90x22) mm<br>Other: contact us.                             |
| <b>Tolerances</b>         | Width: $\pm 1.5$ mm ;<br>Length: $\pm 1.5$ mm.                              |
| <b>Finishing material</b> | Lacquered pinewood<br>(natural or stained lacquered).<br>Other: contact us. |
| <b>Water-resistant</b>    | Ask for properties.                                                         |
| <b>Fire-rated</b>         | UNE 13501: B-s1,d0<br>Autoclave treatment.                                  |

\*Ask for other finishes or sizes.

#### ADDITIONAL FEATURES

|                              |                                                                   |
|------------------------------|-------------------------------------------------------------------|
| <b>Washable Product</b>      | Clean with a damp cloth.<br>Do not use chemical agents.           |
| <b>Impact Resistance</b>     | Depends on the support material.                                  |
| <b>Scratching Resistance</b> | Depends on the finishing material.                                |
| <b>Dirt Proof</b>            | High resistance to dirt.<br>May vary with the finishing material. |
| <b>Recyclable</b>            | Environmentally friendly.                                         |
| <b>Earthquake-resistant</b>  | Possible to install an anti-seismic system.                       |

#### INSTALLATION STANDARD SYSTEM


##### Walls

Fastening clip.



##### Suspended ceilings

Roof anchor, support of the bar and pin.



#### PRODUCT REMARKS

The goods should be stored in the jobsite at least 24h prior to the installation. The temperature must be between 18° and 25° and the relative humidity between 40% and 60%.